

S. V COATINGS PVT LTD

Technical Data Sheet

POLYVAR--815

A high performance quick drying, single pack primer specially formulated by using zinc chromate pigments. The version contains red oxide of iron apart from zinc chromate. It is compatible with a wide range of top coats. The primer gives excellent adhesion to steel.

| | |
|--------------------------------|---|
| Colour | Red Oxide |
| finish | Matt to eggshell |
| Solids | 60 +/- 5 |
| Coverage | 15-16 sq mts/ltr/coat |
| Drying Time | Touch Dry 5-10min Handleable in 3-4 Hours |
| Flash paint | Above 30 deg Centigrade |
| Recommended dry film thickness | 30-40 Microns Per coat. |
| Method of application | Brush / Spray |
| Interval before over coating | 4 hr minimum |
| Surface preparation | Requires wire brushing or acid pickling. |
| Uses | General maintenance primer for Marine Installations, fertilizer plants, pulp & paper mills, bridges, Engineering Industries, power plants, ship construction, oil Refineries, etc . |
| Thinner | Polyvar-31 |
| Storage life | 9 months |

Disclaimer : To the best of our Knowledge the information provided herein are true and accurate at the date of issues. Since we have no control over the quality or condition of the substrate or the various factors affecting the use and application of the product. We do not accept any responsibility or liability arising out of use of the product. The Company reserves the right to modify data contained herein without prior notice.

November 2016